

**300**

⠠⠠⠠⠠⠠⠠

Standard Room #  
3x4



**RESTROOM**

⠠⠠⠠⠠⠠⠠

Standard Unisex Restroom  
Pictogram  
6x8

**LAUNDRY**

⠠⠠⠠⠠⠠⠠

Standard Room Name  
3x8, 3x10, 4x8 & 4x10  
\*number of characters depicts size



**STAIRS**

⠠⠠⠠⠠⠠⠠

Standard Stair & Floor ID  
6x6

**HOLLAND ENGRAVING**

Akron NY

**ADA COMPLIANT GRADE 2**  
**BRAILLE**

Lettering: Larger than .625"

Material: Single ply, modified acrylic;  
1/16" thick backer, 1/32" thick lettering

Finish: "Matte, non-glare, ADA"

Engraving Method: Laser and rotating  
carbide

Usage: Interior and exterior signage

**Physical Properties:**

ADA Substrate material softens sufficiently at about 200°F (93.33°C), which enables bending, should that be desired. It can also be drilled, sawed, sheared, nailed and bonded to itself or other materials.

The material was tested for flammability by Underwriters Laboratories. The materials are rated 94 HB on the UL 94 test. The material was judged as not contributing to the combustion of the base material.

Tensile Strength: 5,500 psi

Rockwell Hardness: M45